



Brass Ball Valve For Potable Water
Two Piece
Full Port
200 psig @ 250°F†
Press x Press Ends With Extension Stem & Memory Stop
Blow-Out Proof Stem


UPBA-481S* ½"-2"



MATERIALS LIST

MATERIALS LIST								
ITEM	PART	MATERIALS	ASTM SPEC.					
1	Body	Brass, Forged	B283 C27450					
2	Tailpiece	Brass, Forged	B283 C27450					
3	Ball	316 Stainless Steel	A276 S31600					
4	Ball Seat	PTFE	Commercial					
5	Stem	316 Stainless Steel	A276 S31600					
6	Stem O-Ring	Buna-N	D2000					
7	Thrust Washer	PTFE	Commercial					
8	Gland Nut	Brass	B124					
9	Packing	PTFE	Commercial					
10	Handle	Zinc Plated Steel	B633					
11	Handle Bolt	Zinc Plated Steel	Commercial					
12	Tube O-Ring	EPDM	D2000					
13	Stem Stop Plate	Zinc Plated Steel	Commercial					
14	Internal Extension Tube	Zinc Plated Steel	Commercial					
15	External Extension Tube	Zinc Plated Steel	Commercial					
16	Upper Stem Adaptor	Zinc Plated Steel	Commercial					
17	Memory Stop	Zinc Plated Steel	Commercial					

*Ultra Press Valves are designed and qualified for use in copper tubing systems only, Types K, L & M per ASTM B88.



DIMENSIONS

	UNITS	1/2" DN15	3/4" DN20	1" DN25	1-1/4" DN32	1-1/2" DN40	2" DN50
۸	INCHES	0.51	0.76	0.98	1.26	1.50	2.01
A	mm	13	19	25	32	38	51
В	INCHES	3.16	3.71	4.28	5.20	6.31	7.44
Ь	mm	80	94	109	132	160	189
С	INCHES	1.63	1.92	2.18	2.75	3.40	3.96
	mm	41	49	55	70	86	101
D	INCHES	3.87	4.26	4.46	4.71	4.87	5.38
	mm	98	108	113	120	124	137
E	INCHES	3.15	4.33	4.33	5.12	5.12	6.89
	mm	80	110	110	130	130	175
G	INCHES	1.52	1.73	2.31	3.16	3.49	4.28
L G	mm	39	44	59	80	89	109
Cv		18	40	72	112	161	287

†Non-Shock

Note: Lead free refers to the wetted surface of the pipe, fittings and fixtures in potable water systems that have a weighted average lead content ≤0.25%. Source: California Health and Safety Code (116875).